


## Indoor Unheated Emergency Safety Shower

EXP-18G(D)  
EXP-18GS(D)

Floor mounted unheated emergency safety shower. ANSI compliant model ideal for use in indoor applications not subject to the possibility of freezing or overheating.

Delivers the ANSI recommended 76 litres per minute of potable water. Available with either galvanised powder coated mild steel (G) or stainless-steel (GS) pipework.



### Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel (GS) or galvanised mild steel (G)
OPERATING VALVE	Stainless steel, full bore, stay open ball valve (GS) or nickel plated brass, two piece stay open valve (G)
SHOWER NOZZLE	Injection moulded nylon 6
STANDARD FINISH	De-scaled (GS) or green powder coated (G)
SERVICES	
WATER INLET	1 1/4" Female BSP
OPERATING PRESSURE	1.5 to 6 BAR G / 22 to 87 PSI
MINIMUM FLOW RATES	76 L per minute / 20 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
SHOWER	Pull handle
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	150mm (5.9in) x 750mm (29.5in) x 2320mm (91.3in)
WEIGHT	12kg (26lb)

# General Arrangement Drawing

## Indoor Unheated Emergency Safety Shower

EXP-18G(D)

EXP-18GS(D)

